

Multi-Bowl Wellhead System

SWECO's Multi-Bowl Systems support and seal two strings of pipe in a single head. They consist of two pieces: a lower housing and an upper housing-installed as one complete unit. If the intermediate casing sticks, the mandrel casing hanger can not be used. The two housings can be separated and the emergency slip-style casing hanger can easily be installed.

SWECO's Multi-Bowl Systems come complete with wear bushings, running tools, standard and emergency packoff, and combination test plug/running-retrieving tool.

Features

- Field proven
- Saves rig time by reducing installation time
- Increases safety by reducing BOP / diverter handling
- Fluted mandrel casing hanger allows cement returns

Outlets

- Studded Side Outlets

Flexibility

- Standard equipment
- Emergency equipment

Manufacturing Standard

- API-6A

Availability

- 11" 5,000 psi wp systems
- 11" 10,000 psi wp systems
- 13-5/8" 5,000 psi wp systems
- 13-5/8" 10,000 psi wp systems
- 10-3/4", 9-5/8" and 8-5/8" surface casing compatibility
- 7-5/8" and 7" intermediate casing compatibility
- 2-7/8" and 2-3/8" tubing compatibility
- Additional sizes available upon request

Bottom Connections

- Slip-on weld
- Slip-on weld with O-ring
- Threaded (8rd, Buttress)

